

01-5G 1-pack/2-pack

5GHz 9dBi 11AC 867Mbps Outdoor CPE

Product Information	
Model	O1-5G
Dimension	132*72*46.3mm
Deployment	Pole/Wall Mount
Application Scenarios	PtP and PtMP wireless connection for Privated ISP access or CCTV Surveillance
Hardware	
Frequency Range	5GHz
Compliant Standards	IEEE 802.11a/n/ac
Maximum Wireless Rate	867Mbps
Interfaces	1*10/100Mbps LAN Port
Antenna Polarization	Dual Polarization
Antennas Gain	9dBi
Antenna Beamwidth	Horizontal: 30° Vertical: 30° Elevation: 30°
GND	-
Reset Button	1*Reset Button
Power Consumption	4.7W
Waterproof Level	IP65
LED Indicator	PoE/LAN,LED1,LED2
Power Method	12V 1A Passive PoE 12V 1A DC

Lightning Protection	-
Passive PoE	Passive power over ethernet via PoE/LAN (+4,5pins -7,8pins) up to 60 meters Voltage range: 9-13V DC
Reception Sensitivity	11a 6Mbps -92dBm±1.5dBm 11n MCS7 HT20 -72dBm±1.5dBm 11ac MCS9 HT80 -64dBm±1.5dBm
Software	
TDMA	-
Operating mode	AP/Station
Enable/Disable Wireless Radio	Support
SSID Hidden	Support
Wireless Client isolation	Support
SSID Isolation	-
Channel Bandwidth	20/40/80MHz
Channel Shift	Support
Client Limitation For SSID	Support
Wireless Access Control	Support
Weak Signal Client Limitation	-
Transmission Power	Adjustable power by 1dBm
WMM Capable	Support
APSD Capable	Support
Wireless Security	64/128 WEP,WPA-PSK,WPA2-PSK,WPA&WPA2-PSK
Transparent Bridge	Support

VLAN Tagging for SSID	-
DHCP Server	-
VPN Pass-Through	PPTP,L2TP
Remote Web access	-
Schedule Reboot	Support
Page Timeout	Support
Ping Watchdog	Support
Dyndns	-
Network Diagnoses	-
Time and Date Setting	Support
Firmware upgrade	Support
Backup/Restore Configuration	Support
Username Managerment	Support
System Logs	Support
Managed By Controller	PC Software -- CPE Assistant
Others	
Package Contents	1*5GHz 9dBi 11AC 867Mbps Outdoor CPE 1*Power Adapter 1*PoE Injector 1*Quick Installation Guide
Operation Temperature	-30°C ~ 60°C
Storage Temperature	-40°C ~ 70°C

Operating Humidity	10%~90% non-condensing
Storage Humidity	10%~90% non-condensing
Default login IP	192.168.2.1
Default Login Username	admin
Default Login Password	admin
Certification	FCC/CE/RoHS